

Fiche Technique

COB Fix

Or Argent
Blanc Noir Gris



Caractéristiques:

Taille de découpe	Ø 73mm	Température de couleur	2700K < 6000K -
Min. hauteur encastrée	60mm		2000K->2800K
Poids	142g	Lumen	700 - 720 - 770
IP	20		450->830 lm
Classe d'isolation	II	CRI	≥ 85/85/80/75
Essai du fil incandescent	850 °C	Refroidissement	Passif
RoHS	Oui	Efficience	80 lm/W
Sans UV	Oui	Durée de vie	50.000h
Certification	CE		

Source de lumière:

Température de couleur	2700K < 6000K -
	2000K->2800K
Lumen	700 - 720 - 770
	450->830 lm
CRI	≥ 85/85/80/75
Refroidissement	Passif
Efficience	80 lm/W
Durée de vie	50.000h


Alimentation:

Driver	Inclus
Voltage	230V
Max. puissance	9W


Options:

Barndoors	Non
Nid d'abeille	Non
Filtre UV	Non
Couleurs Filtres	Non
Dimmable	DALI & Phase & Casambi & 0-10V
Eclairage de secours	Non
Fixpoint	Non






Reflectors:



+50mm
Refroidissement



87



Data Sheet

COB Fix

Gold Silver
White Black Grey



Characteristics:

Cut-out size	Ø 73mm	Colour temperature	2700K < 6000K -
Min. recessed height	60mm		2000K->2800K
Weight	142g	Lumen	700 - 720 - 770
IP	20		450->830 lm
Isolation class	II	CRI	≥ 85/85/80/75
Glow wire test	850 °C	Cooling	Passif
RoHS	Yes	Efficiency	80 lm/W
UV free	Yes	Lifetime	50.000h
Certification	CE		

Light source:

Colour temperature	2700K < 6000K -
	2000K->2800K
Lumen	700 - 720 - 770
	450->830 lm
CRI	≥ 85/85/80/75
Cooling	Passif
Efficiency	80 lm/W
Lifetime	50.000h


Power supply:

Driver	Included
Voltage	230V
Max. power	9W


Options:

Barndoors	No
Honeycomb	No
UV filter	No
Colour Filters	No
Dimmable	DALI & Phase & Casambi & 0-10V
Emergency light	No
Fixpoint	No

Reflectors:



+50mm
Cooling



87

